


Cable Glands, Sealing Washers & Locknuts

For use in potentially explosive atmospheres. Manufactured from either Brass, Nickel Plated Brass and Stainless Steel or Nylon and Fibre.

Exe Nylon Gland - Group II, Zones 1, 2, 21 and 22



Certification & Standards

Certification Standard:

Sira 00 ATEX 1072X

Coupler - Female to Female thread couplers for use in both Exd and Exe applications




Certification & Standards

Certification Standard:


Baseefa 08 ATEX 0359U
IECEx BAS08.0121U

Temperature: -60°C to +200°C

Hex Locknut - for Metric Threads and NPT Threads (Nickel Plated Brass only)



Sealing Joint Washer - for use with all ATEX and IECEx approved products (Nylon only)



Certification & Standards

Certification Standard:

Nylon Metric approved for use
with all ATEX / IECEx products

Earth Tag - to be used to create an earthing bond on an enclosure, when a cable gland is used



Cable Glands, Sealing Washers & Locknuts



Technical Specifications

Type	Metric Thread Size (mm)	16	20	25	32	40	50	63	75
	PG Thread Size	$\frac{3}{8}$	$\frac{1}{2}$	$\frac{3}{4}$	1	1 $\frac{1}{4}$	1 $\frac{1}{2}$	2	2 $\frac{1}{2}$
Exe Nylon Gland		EX-8160	EX-8240	EX-8560	EX-8640	EX-8720	EX-8800	-	-

Type	Metric Thread Size (mm)	16	20	25	32	40	50	63	75
	PG Thread Size	$\frac{3}{8}$	$\frac{1}{2}$	$\frac{3}{4}$	1	1 $\frac{1}{4}$	1 $\frac{1}{2}$	2	2 $\frac{1}{2}$
Metric - Brass		EX/M16/C	EX/M20/C	EX/M25/C	EX/M32/C	EX/M40/C	EX/M50/C	EX/M63/C	EX/M75/C
NPT Thread - Brass		EX/038/C	EX/050/C	EX/075/C	EX/100/C	EX/125/C	EX/150/C	EX/200/C	EX/250/P

*For Nickel Plated Brass add EXN and for Stainless Steel add EXS, e.g. EXS/M16/C

Type	Metric Thread Size (mm)	16	20	25	32	40	50	63	75
	PG Thread Size	$\frac{3}{8}$	$\frac{1}{2}$	$\frac{3}{4}$	1	1 $\frac{1}{4}$	1 $\frac{1}{2}$	2	2 $\frac{1}{2}$
Metric - Stainless Steel		-	MXWH04	MXWH05	MXWH06	MXWH07	MXWH08	-	-
Metric - Brass		WHMB03	WHMB04	WHMB05	WHMB06	WHMB07	WHMB08	-	-
Metric - Nickel Plated Brass		WHMM03	WHMM04	WHMM05	WHMM06	WHMM07	WHMM08	WHMM09	-
NPT Thread - Nickel Plated Brass		-	WHAM04	WHAM05	WHAM06	WHAM07	WHAM08	WHAM09	-

Type	Metric Thread Size (mm)	16	20	25	32	40	50	63	75
	PG Thread Size	$\frac{3}{8}$	$\frac{1}{2}$	$\frac{3}{4}$	1	1 $\frac{1}{4}$	1 $\frac{1}{2}$	2	2 $\frac{1}{2}$
	Outside Diameter (mm)	22	26	34.3	41.5	52	66.5	84.5	-
	Thickness (mm)	1.6	1.6	1.7	1.7	2	2	2	-
Metric - Nylon (ATEX / IECEx approved)		EXFM03	EXFM03	EXFM03	EXFM03	EXFM03	EXFM03	EXFM03	-
Metric - Fibre		WHMB03	WHMB04	WHMB05	WHMB06	WHMB07	WHMB08	-	-

Type	Metric Thread Size (mm)	16	20	25	32	40	50	63	75
	PG Thread Size	$\frac{3}{8}$	$\frac{1}{2}$	$\frac{3}{4}$	1	1 $\frac{1}{4}$	1 $\frac{1}{2}$	2	2 $\frac{1}{2}$
Earth Tag - Brass		EX/M16/TAG	EX/M20/TAG	EX/M25/TAG	EX/M32/TAG	EX/M40/TAG	EX/M53/TAG	EX/M63/TAG	EX/M75/TAG