

热缩型端头、中接管、可分断式连接器




热缩性的优势!

- 这些环状端头、对接中接管和可分断式连接器均为自绝缘的，其采用热缩性的聚烯烃并在内部涂覆密封胶。
- 完整安装后，可实现完全密封连接，从而保护接头免受电蚀、腐蚀和环境暴露的影响。


注：未获室外应用认证。

热缩性环形端头



产品编号	包装件数	导线规格范围	最大值 (IN)	螺栓孔	推荐工具	尺寸				材料厚度
						A	B	C	M	
RAS18-6X	100	22-18	.170	#6	ERG4255	1.23	.25	.27	1.10	.03
RAS18-8X	100	22-18	.170	#8		1.26	.31	.27	1.10	
RAS18-10X	100	22-18	.170	#10		1.26	.31	.27	1.10	
RBS14-6X	100	16-14	.200	#6		1.23	.25	.27	1.10	
RBS14-8X	100	16-14	.200	#8		1.23	.25	.27	1.10	
RBS14-10X	100	16-14	.200	#10		1.26	.31	.27	1.10	
RCS10-6X	50	12-10	.250	#6		1.34	.31	.27	1.15	.04
RCS10-8X	50	12-10	.250	#8		1.34	.37	.27	1.15	
RCS10-10X	50	12-10	.250	#10		1.34	.37	.27	1.15	
RCS10-14X	50	12-10	.250	1/4"		1.34	.49	.32	1.15	


热缩性锁定叉形端头



产品编号	包装件数	导线规格范围	最大值 (IN)	螺栓孔	推荐工具	尺寸				材料厚度
						A	B	C	M	
RAS18-6FLX	100	22-18	.170	#6	ERG4255	1.350	.25	—	—	.03
RAS18-8FLX	100	22-18	.170	#8		1.350	.29	—	—	
RAS18-10FLX	100	22-18	.170	#10		1.350	.29	—	—	
RBS14-6FLX	100	16-14	.200	#6		1.350	.25	—	—	
RBS14-8FLX	100	16-14	.200	#8		1.350	.29	—	—	
RBS14-10FLX	100	16-14	.200	#10		1.350	.29	—	—	
RCS10-6FLX	50	12-10	.250	#6		1.350	.31	—	—	.04
RCS10-8FLX	50	12-10	.250	#8		1.350	.37	—	—	
RCS10-10FLX	50	12-10	.250	#10		1.350	.37	—	—	
RCS10-14FLX	50	12-10	.250	1/4"		1.350	.49	—	—	


热缩型端头、中接管、可分断式连接器

热缩性全绝缘孔式可分断式连接器




产品编号	包装件数	导线规格范围	最大值(IN)	插片尺寸	推荐工具	A
RAS18-250AX	25	22-18	.170	.250 x .032	ERG4255	1.82
RBS14-250AX	25	16-14	.200	.250 x .032		1.77
RCS10-250AX	25	12-10	.250	.250 x .032		1.80

热缩性全绝缘针式接头



产品编号	包装件数	导线规格范围	最大值(IN)	插片尺寸	推荐工具	A
18RAS-251TX	25	22-18	.170	.250 x .032	ERG4255	1.80
14RBS-251TX	25	16-14	.200	.250 x .032		1.75
10RCS-251TX	25	12-10	.250	.250 x .032		1.80

热缩性对接中接管



产品编号	包装件数	导线规格范围	最大值(IN)	推荐工具	尺寸	
					A	B
2RAS18X	50	22-18	.170	ERG4255	1.50	.25
RAAS22X	500	22-18	.170		1.50	.25
2RBS14X	50	16-14	.200		1.50	.26
RBBS22X	500	16-14	.200		1.50	.26
2RCS10X	25	12-10	.250		1.60	.31
RCCS22X	250	12-10	.250		1.60	.31



你需要用一个方便的工具制成完全密封的连接

热缩性端头工具套件

- 工具: (1)丁烷喷灯; (1)剥线钳; (1)棘齿卷边工具
- 对接中接管: (20) #22-#18 AWG、(20) #16-#14 AWG、(15) #12-#10 AWG
- 环形端头: (20) #16-#14 AWG #10螺柱; (2) #16-#14 AWG #8螺柱; (15) #12-#10 AWG 1/4" 螺柱

产品编号	说明	标准包装件数
STAPOUCH-HS	热缩性端头工具套件	1