


**Technical Description**

This coupling system has been developed specifically for the area of breathing protection.

Coupling system with single-hand operation. UltraFlo valve for optimum flow and low pressure drop. Additional safety locking system. This safety lock prevents unintentional disconnection. To disconnect, the plug must first be pushed further into the coupling before it can be unlocked.

Profile cannot be interconnected with the 96KS series. Tested according EN 139 standard.

**Dust Protections**  (P. 319)  
for Coupling Part.-No. SK23S

**Working Temperature\***

-20°C up to +100°C (NBR)  
depending on the medium.

\* For temperatures below -20°C and over +100°C and depending on the medium, other seal variants (FKM, EPDM, FFKM) are available.

**Working Pressure\*\***

35 bar

\*\* maximum static working pressure with safety factor 4 to 1.

**Material**


**Coupling:** Brass / Stainless Steel  
or Brass nickel plated

**Plug:** Steel nickel plated

**Seals:** NBR

**Flow diagrams**




**Air**





# Couplings – with valve




# Series 95KS

	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	R 1/4	19		61	12		23			nickel plated	95KSAK13BPN
	R 1/4	19		61	12		23			Stainless Steel	95KSAK13RPN
	R 3/8	19		60	12		23			nickel plated	95KSAK17BPN
	R 3/8	19		60	12		23			Stainless Steel	95KSAK17RPN
	R 1/2	22		61	17		23			nickel plated	95KSAK21BPN
	R 1/2	22		61	17		23			Stainless Steel	95KSAK21RPN
 <p>Female Thread</p>	G 1/4	19		56	10		23			nickel plated	95KSIW13BPN
	G 1/4	19		56	10		23			Stainless Steel	95KSIW13RPN
	G 3/8	19		55	9		23			nickel plated	95KSIW17BPN
	G 3/8	19		55	9		23			Stainless Steel	95KSIW17RPN
	G 1/2	24		58	12		23			nickel plated	95KSIW21BPN
	G 1/2	24		58	12		23			Stainless Steel	95KSIW21RPN
 <p>Hose Barb</p>	6 mm	19		74	25		23			nickel plated	95KSTF06BPN
	7 mm	20		77	22		23			nickel plated	95KSTF07BPN
	8 mm	19		74	25		23			nickel plated	95KSTF08BPN
	9 mm	19		74	25		23			nickel plated	95KSTF09BPN
	9 mm	19		74	25		23			Stainless Steel	95KSTF09RPN
	10 mm	19		74	25		23			nickel plated	95KSTF10BPN
	10 mm	19		74	25		23			Stainless Steel	95KSTF10RPN
	13 mm	19		74	25		23			nickel plated	95KSTF13BPN



# Plugs – without valve

# Series 95KS

	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	R 1/4	14		38,5	12						95SSAK13MXN
	R 3/8	17		38,5	12						95SSAK17MXN
 <p>Female Thread</p>	G 1/4	17		33	9						95SSIW13MXN
	G 3/8	19		33	9						95SSIW17MXN
 <p>Hose Barb</p>	6 mm			47,5	25		14				95SSTF06MXN
	9 mm			47,5	25		14				95SSTF09MXN
	10 mm			47,5	25		14				95SSTF10MXN