


Stud Fittings

3669

Extended Stud Elbow, Male BSPP and Metric Thread



FDA chemical nickel-plated brass, FKM



ØD	C		E	F	G	H	J	L	kg
4	M5x0.8	3669 04 19	3.5	10	10	27.5	7	18	0.014
	G1/8	3669 04 10	5.5	13	10	25.5	7	18	0.017
6	G1/8	3669 06 10	5.5	13	12	31	8	21.5	0.024
	G1/4	3669 06 13	6.5	16	12	30.5	8	21.5	0.028
8	G1/8	3669 08 10	5.5	14	15	33.5	10	23.5	0.031
	G1/4	3669 08 13	5.5	16	15	34	10	23.5	0.035
10	G1/4	3669 10 13	6.5	18	17.5	42	12	29	0.052
	G3/8	3669 10 17	7.5	20	17.5	41	12	29	0.056
12	G1/4	3669 12 13	6.5	20	19.5	47	15	31	0.070
	G3/8	3669 12 17	7.5	20	19.5	46	15	31	0.072
14	G1/2	3669 14 21	9	24	21.5	49	16	34	0.094


The body swivels for positioning purposes.

3608

Stud Branch Tee, Male BSPT Thread



FDA chemical nickel-plated brass, FKM



ØD	C		F	G	H	J	L/2	kg
4	R1/8	3608 04 10	10	10	24.5	7	18	0.020
	R1/4	3608 06 10	13	12	29.5	8	21.5	0.031
6	R1/4	3608 06 13	14	12	30.5	8	21.5	0.038
	R1/8	3608 08 10	14	15	32.5	10	23.5	0.040
8	R1/4	3608 08 13	14	15	34	10	23.5	0.047
	R1/4	3608 10 13	18	17.5	39	12	29	0.067
10	R3/8	3608 10 17	18	17.5	41	12	29	0.070
	R3/8	3608 12 17	20	19.5	46.5	15	31	0.094
14	R1/2	3608 14 21	22	21.5	50.5	16	34	0.125


The body swivels for positioning purposes.

3603

Stud Run Tee, Male BSPT Thread



FDA chemical nickel-plated brass, FKM



ØD	C		F	G	H	H1	J	L	kg
4	R1/8	3603 04 10	10	10	19.5	18	7	23	0.018
	R1/8	3603 06 10	13	12	23.5	21.5	8	28	0.031
6	R1/4	3603 06 13	14	12	24.5	21.5	8	28	0.037
	R1/8	3603 08 10	14	15	25	23.5	10	31	0.041
8	R1/4	3603 08 13	14	15	26.5	23.5	10	31	0.044
	R1/4	3603 10 13	18	17.5	30.5	29	12	37.5	0.067
10	R3/8	3603 10 17	18	17.5	32.5	29	12	37.5	0.069
	R3/8	3603 12 17	20	19.5	36.5	31	15	40.5	0.103
14	R1/2	3603 14 21	22	21.5	40	34	16	45	0.147


The body swivels for positioning purposes.

3698

Stud Branch Tee, Male BSPP and Metric Thread



FDA chemical nickel-plated brass, FKM






ØD	C		E	F	G	H	J	L/2	kg
4	M5x0.8	3698 04 19	3.5	10	10	27.5	7	18	0.018
	G1/8	3698 04 10	5.5	13	10	25.5	7	18	0.021
6	G1/8	3698 06 10	5.5	13	12	31	8	21.5	0.031
	G1/4	3698 06 13	6.5	16	12	30.5	8	21.5	0.035
8	G1/8	3698 08 10	5.5	14	15	33.5	10	23.5	0.041
	G1/4	3698 08 13	6.5	16	15	34	10	23.5	0.045
10	G1/4	3698 10 13	6.5	18	17.5	42	12	29	0.066
	G3/8	3698 12 17	7.5	20	19.5	46	15	31	0.088
14	G1/2	3698 14 21	9	24	21.5	49	16	34	0.111

The body swivels for positioning purposes.




Stud Fittings

3693 Stud Run Tee, Male BSPP and Metric Thread

	FDA chemical nickel-plated brass, FKM				E	F	G	H	H1	J	L	kg
	ØD	C										
	4	M5x0.8	3693 04 19		3.5	10	10	22.5	18	7	23	0.019
		G1/8	3693 04 10		5.5	13	10	20.5	18	7	23	0.021
	6	G1/8	3693 06 10		5.5	13	12	25	21.5	8	28	0.031
		G1/4	3693 06 13		6.5	16	12	24.5	21.5	8	28	0.035
	8	G1/8	3693 08 10		5.5	14	15	26.5	23.5	10	31	0.041
		G1/4	3693 08 13		6.5	16	15	26.5	23.5	10	31	0.044
	10	G1/4	3693 10 13		6.5	18	17.5	33	29	12	37.5	0.066
	12	G3/8	3693 12 17		7.5	20	19.5	36.5	31	15	40.5	0.090
	14	G1/2	3693 14 21		9	24	21.5	38.5	34	16	45	0.112

The body swivels for positioning purposes.

3618 Single Banjo, Male BSPP and Metric Thread

	FDA chemical nickel-plated brass, FKM				F	H	H1	J	L1	L2	kg
	ØD	C									
	4	M5x0.8	3618 04 19		8	14.5	6.5	10	6	18.5	0.011
		G1/8	3618 04 10		14	23	9.5	17	10	20.5	0.029
		M5x0.8	3618 06 19		8	15	7	10	6	22.5	0.015
	6	G1/8	3618 06 10		14	23	9.5	17	10	23.5	0.031
		G1/4	3618 06 13		17	22	9	22	13	25.5	0.049
	8	G1/8	3618 08 10		14	23	9.5	17	10	26	0.033
		G1/4	3618 08 13		17	22	9	22	13	27.5	0.051
	10	G3/8	3618 10 17		22	33	14	22	13	32	0.105




Maximum temperature: +80°C

Each model has been designed to meet specific requirements: compactness due to small overall dimensions, with inter-connectability for customised configurations.






Tube-to-Tube Fittings




3606 Equal Tube-to-Tube Connector

			FDA chemical nickel-plated brass, FKM			
			ØD	G	L	kg
			4	3606 04 00	10 30.5	0.010
			6	3606 06 00	12 36.5	0.016
			8	3606 08 00	15 37.5	0.021
			10	3606 10 00	17.5 47.5	0.034
			12	3606 12 00	19.5 50	0.042
			14	3606 14 00	21.5 52.5	0.050

3602 Equal Elbow




			FDA chemical nickel-plated brass, FKM			
			ØD	G	L	kg
			4	3602 04 00	10 23	0.010
			6	3602 06 00	12 28	0.016
			8	3602 08 00	15 31	0.023
			10	3602 10 00	17.5 37.5	0.033
			12	3602 12 00	19.5 40.5	0.045
			14	3602 14 00	21.5 45	0.056

3604 Equal Tee




			FDA chemical nickel-plated brass, FKM			
			ØD	G	H	L/2
			4	3604 04 00	10 23 18	0.014
			6	3604 06 00	12 28 21.5	0.023
			8	3604 08 00	15 31 23.5	0.032
			10	3604 10 00	17.5 37.5 29	0.048
			12	3604 12 00	19.5 40.5 31	0.063
			14	3604 14 00	21.5 45 34	0.078

Bulkhead Connector Fittings




3616 Equal Bulkhead Connector

	<p>FDA chemical nickel-plated brass, FKM</p> 	ØD		F1	F2	K	L1	L2	ØT min	kg
		4	3616 04 00	13	14	14	14	20	12.5	0.018
		6	3616 06 00	16	17	17.5	17	22	15	0.028
		8	3616 08 00	18	19	19.5	18.5	23.5	17	0.035
		10	3616 10 00	22	27	24	21.5	26.5	21	0.063
		12	3616 12 00	24	24	26	23	27	23	0.062
		14	3616 14 00	27	27	29.5	25.5	29.5	25	0.079

3636 Bulkhead Connector, Female BSPP Thread

	<p>FDA chemical nickel-plated brass, FKM</p> 	ØD	C		E	F1	F2	H	H1	K	ØT min	kg
		4	G1/8	3636 04 10	8.5	14	14	30.5	11	15	13	0.020
		6	G1/8	3636 06 10	8.5	17	17	33	11	18.5	15	0.033
			G1/4	3636 06 13	11.5	17	17	37	15	18.5	15	0.033
		8	G1/8	3636 08 10	8.5	19	19	34	10.5	21	17	0.044
			G1/4	3636 08 13	11.5	19	19	38	14.5	21	17	0.044
		10	G3/8	3636 10 17	12	22	27	42.5	16	24	21	0.073
G3/8	3636 12 17		12	24	24	43	16	26	23	0.077		
12	G1/2	3636 12 21	16	27	24	48.5	21.5	29.5	23	0.133		

3639 Equal Bulkhead Elbow

	<p>FDA chemical nickel-plated brass, FKM</p> 	ØD		F1	F2	G	H	K	L	ØT min	kg
		4	3639 04 00	13	14	10	35	14	18	12.5	0.023
		6	3639 06 00	16	17	12	40.5	17.5	21.5	15	0.035
		8	3639 08 00	18	19	15	44	19.5	23.5	17	0.046
		10	3639 10 00	22	27	17.5	51	24	29	21	0.080
		12	3639 12 00	24	24	19.5	55	26	31	23	0.086
		14	3639 14 00	27	27	21.5	59	29.5	34	25	0.144

The body swivels for positioning purposes.