





## TEMA AIR COUPLING Series 1600




Coupling Female Thread




Coupling Male Thread




Coupling incl. Hose Nipple




Hose Nipple




Plug-in Nipple Male Thread




Plug-in Nipple Female Thread




Plug-in Nipple w/ Hose Connection



Safety Nipple w/ Hose Connection



Safety Nipple Male Thread



Safety Nipple w/ Hose Socket

Type	Part No.	Dimension ISO-BSP		Min. Through-put mm	Rubber Quality	D mm	L mm	WS mm	Max Work. Pres. bar	Hose Inside Diameter		Weight gr.
		Male	Female							mm	inches	
Coupling	1600		1/4	7.5	nitrile	23	58	19	30			108
	1600 A	3/8		7.5	nitrile	23	59	19	30			98
	1600 B		3/8	7.5	nitrile	23	57	20	30			106
	1600 C	1/2		7.5	nitrile	23	61	23	30			125
	1600 D	1/4		7.5	nitrile	23	61	19	30			100
	1600 F		1/2	7.5	nitrile	23	57	25	30			127
Coupling incl. Hose Nipple	1600 K06			4.8	nitrile	23	80	19	30	6	1/4"	113
	1600 K08			6.4	nitrile	23	80	19	30	8	5/16"	114
	1600 K10			7.5	nitrile	23	80	19	30	10	3/8"	115
	1600 K12			7.5	nitrile	23	79	19	30	12	1/2"	115
Hose Nipple <sup>1)</sup> I	1306	1/4					37	16	30	6	1/4"	16
	1308	1/4					37	16	30	8	5/16"	17
	1310	1/4					37	16	30	10	3/8"	19
	1312	1/4					38	16	30	12	1/2"	21
	1806	3/8					38	19	30	6	1/4"	21
	1808	3/8					38	19	30	8	5/16"	23
	1810	3/8					38	19	30	10	3/8"	25
Plug-in Nipple II Male Thread	1812	3/8					39	19	30	12	1/2"	29
	16110	1/8				10	32	13	30			14
	16210	1/4				10	38	14	30			20
	16220	3/8				10	36	19	30			24
Plug-in Nipple III Female Thread	16230	1/2				10	40	22	30			34
	16405		1/8			10	30	13	30			13
	16410		1/4			10	36	16	30			21
Plug-in Nipple IV w/ Hose Connection	16420		3/8			10	36	20	30			28
	16430		1/2			10	40	25	30			48
	16006					10	43		30	6	1/4"	12
Safety Nipple V	16008					10	43		30	8	5/16"	13
	16010					10	43		30	10	3/8"	15
	16012					10	46		30	12	1/2"	22
	16006 S					10	73	20	30	6	1/4"	46
Safety Nipple combined with Hose Socket VI	16008 S					10	73	20	30	8	5/16"	48
	16010 S					10	73	20	30	10	3/8"	49
	16012 S					10	74	20	30	12	1/2"	53
	16210 S	1/4				10	60	20	30			49
Plastic Protection Coupling Nipple	16006 S-1					10	69	20	30	6	1/4"	62
	16008 S-1					10	69	20	30	8	5/16"	64
	16010 S-1					10	69	20	30	10	3/8"	68
O-ring	1316				PVC							5
	1326				PVC							3
	N7-9,3				nitrile							
Fiber Gasket	13320											

<sup>1)</sup> 1306-1312 fits 1600  
1806-1812 fits 1600 B  
<sup>2)</sup> Interchangeable with Cejn 320, Luna 25, OBAC 25, Rectus 25, Bosch 825



Fiber Gasket

