## Catalog 3900 - Agricultural Couplings

# 8450 Series Push/Pull Sleeve Design

Connect under pressure and rigid mount





Pioneer's 8450 Series unique valve design allows connection while either or both the coupler and nipple are under pressure. Valves in both halves remain closed, opening only when system pressure has been relieved on the female body and then

reapplied. This pressure sequence may be done with either an open center or a closed center hydraulic system that has a control valve. The enclosed outer housing allows all connecting motion to be internal thereby preventing dust and dirt build-up around the sleeve mechanism. Suitable for rigid mount or use with a breakaway clamp.

#### Features:

- Accepts ISO 5675 universal tips
- Straight thread ORB fitting end allows direct mounting to a control valve or rigid tubing
- Outer housing keeps dust and dirt away from the sleeve mechanism
- Connect under system pressure on the coupler side and on the nipple side
- One-handed push-to-connect operation when coupler is clamp or rigid mounted
- Couplers are compatible with 5006-4 breakaway clamps
- Protective zinc plating with clear trivalent chromate finish

### Applications include:

- Tractors
- Mid-sized agricultural equipment

8450 Series Specifications												
Body Size	Rated Flow	Rated Pressure	Temperature		Body Materia	l Sleeve Type	Seal Material					
1/2"	25 gpm	3000 psi	-40° F to +250° F		Steel	Rigid Mount	Nitrile					
	Connect Force				Disconnect Force							
70 lbs. max at 0 psi 100 lbs. max at 3000 psi				40 lbs. min at 0 psi 165 lbs. max at 3000 psi								

#### 8450 Series Couplers Body Coupler Sleeve Port End Flats Clamp to Use **Dust Plug** Valve Type Part Number Diameter Size 8450-16 7/8-14 ORB (Female) 1.38 1.50 5006-4 8405-4 or 8407-4 1/2 **Poppet** 1/2 8450-16M 7/8-14 ORB (Male) **Poppet** 1.38 1.50 5006-4 8405-4 or 8407-4

8010 Series Nipples												
4	TEMET	Poppet	Ball \	/alve See pag	See page A-2 for additional ISO 5675 tip options.							
Body Size	Coupler Part Number	Port End	Valve Type	Length	Largest Diameter	Wrench Flats	Weight (lbs.)					
1/2	8010-16	7/8-14 ORB (Female)	Ball	1.95	1.23	1.06	0.25					
1/2	8010-16P	7/8-14 ORB (Female)	Poppet	1.95	1.23	1.06	0.25					



