



Body Size

1/4" to 1"

Tema Profile

FF-Series



Connected length in total

FF2510 + FF2520 = 122 mm

FF2510 + FF2521 = 147 mm

FF3810 + FF3820 = 125 mm

FF3810 + FF3821 = 154 mm

FF5010 + FF5020 = 144 mm

FF5010 + FF5021 = 179 mm

FF7510 + FF7520 = 169 mm

FF7510 + FF7521 = 215 mm

FF10010 + FF10020 = 230 mm

FF10010 + FF10021 = 269 mm

Body Size Bursting Pressure connected

1/4" > 3200 bar

3/8" > 2000 bar

1/2" > 1500 bar

3/4" > 1500 bar

1" > 1100 bar

Applications Area



Technical Description

The coupling system of the FF series has double shut-off, dry break and single-handed operation. During disconnection there is no oil loss, and during coupling there is no inclusion of air into the system.

Advantages

Dry break quick connect coupling. With minimum pressure drop. Single-handed operation. No oil loss during disconnection. A safety closing ring prevents unintentional disconnection. Twice as safe through double sealing. Also available with pressure eliminator, i.e. connection is possible under static/residual pressure up to working pressure.

Working Pressure

See charts.

Working Temperature






-30°C up to +100°C (NBR)
-25°C up to +200°C (FKM)
depending on the medium.
Special seals are available on request (see page 6).

Available Valves



Material Coupling	Standard / Pressure Eliminator
Coupling Body	Steel, nitrocarburizing
Sleeve	Steel hardened, zinc plated, passivated, sealed
Looking Ring	Brass, zinc-iron coated, black passivated, sealed
Valve	Steel, zinc plated, passivated, sealed
Springs	AISI 301
Locking Balls	AISI 420 C
Seals	NBR/PUR
Valve Holder	Steel, yellow zinc plated, sealed
Thread Body	Steel, zinc plated, passivated, sealed
Plug	Standard / Pressure Eliminator
Plug Body	Steel hardened, zinc plated, passivated, sealed
Valve	Steel, nitrocarburizing
Springs	AISI 301
Seals	NBR/PUR
Valve Holder	Brass, hard-drawn
Thread Body	Steel, zinc plated, passivated, sealed

Flow Capacity with Oil with Viscosity of 32cSt at 40°C as per ISO 7241/2-2000




— Standard FF
- - - Plug side pressure eliminator

Couplings

FF-Series Standard

Body Size	Connection A	Hex mm	L mm	D mm	Working Press. connect. in bar	Version	Seal	Part Number
1/4"	G 1/4	27	65	30	800	Standard	NBR/PUR	FF2510
3/8"	G 3/8	36	76,5	40	500	Standard	NBR/PUR	FF3810
1/2"	G 1/2	40	82	44	400	Standard	NBR/PUR	FF5010 C
1/2"	G 1/2	40	82	44	400	Standard	FKM	FF5010 CV
1/2"	G 3/4	40	82	44	400	Standard	NBR/PUR	FF5010-75 C
1/2"	G 3/4	40	82	44	400	Standard	FKM	FF5010-75 CV
3/4"	G 3/4	50	98	55	400	Standard	NBR/PUR	FF7510 C
3/4"	G 3/4	50	98	55	400	Standard	FKM	FF7510 CV
3/4"	G 1	50	106	55	400	Standard	NBR/PUR	FF7510-100 C
3/4"	G 1	50	106	55	400	Standard	FKM	FF7510-100 CV
1"	G 1	65	120	70	300	Standard	NBR/PUR	FF10010 C
1"	G 1	65	120	70	300	Standard	FKM	FF10010 CV
1"	G 1 1/4	65	120	70	300	Standard	NBR/PUR	FF10010-125 C
1"	G 1 1/4	65	120	70	300	Standard	FKM	FF10010-125 CV
1"	G 1 1/2	65	120	70	300	Standard	NBR/PUR	FF10010-150 C
1"	G 1 1/2	65	120	70	300	Standard	FKM	FF10010-150 CV




Female Thread

Plugs


FF-Series Standard

Body Size	Connection A	Hex mm	L mm	D mm	Working Press. connect. in bar	Version	Seal	Part Number
1/4"	G 1/4	25	74	28	800	Standard	NBR/PUR	FF2520
3/8"	G 3/8	32	69	35	500	Standard	NBR/PUR	FF3820
1/2"	G 1/2	36	84	35	400	Standard	NBR/PUR	FF5020 C
1/2"	G 1/2	36	84	35	400	Standard	FKM	FF5020 CV
1/2"	G 3/4	36	90	40	400	Standard	NBR/PUR	FF5020-75 C
1/2"	G 3/4	36	90	40	400	Standard	FKM	FF5020-75 CV
3/4"	G 3/4	41	101	45	400	Standard	NBR/PUR	FF7520 C
3/4"	G3/4	41	101	45	400	Standard	FKM	FF7520 CV
3/4"	G 1	50	112	55	400	Standard	NBR/PUR	FF7520-100 C
3/4"	G 1	50	112	55	400	Standard	FKM	FF7520-100 CV
1"	G 1	60	138	65	300	Standard	NBR/PUR	FF10020 C
1"	G 1	60	138	65	300	Standard	FKM	FF10020 CV
1"	G 1 1/4	60	138	70	300	Standard	NBR/PUR	FF10020-125 C
1"	G 1 1/4	60	138	70	300	Standard	FKM	FF10020-125 CV
1"	G 1 1/2	60	138	70	300	Standard	NBR/PUR	FF10020-150 C
1"	G 1 1/2	60	138	70	300	Standard	FKM	FF10020-150 CV




Female Thread


Plugs FF-Series Pressure Eliminator

	Body Size	Connection A	Hex mm	L mm	D mm	D1 mm	Working Press. connect. in bar	Version	Seal	Part Number
 <p>Female Thread</p>	1/4"	G 1/4	25	99	28		800	Press. Eliminator	NBR/PUR	FF2521
	3/8"	G 3/8	32	98	35		500	Press. Eliminator	NBR/PUR	FF3821
	1/2"	G 1/2	36	120	40		400	Press. Eliminator	NBR/PUR	FF5021 C
	1/2"	G 1/2	36	120	40		400	Press. Eliminator	FKM	FF5021 CV
	3/4"	G 3/4	50	146	56		400	Press. Eliminator	NBR/PUR	FF7521 C
	1"	G 1	55	178	60		300	Press. Eliminator	NBR/PUR	FF10021 C


Couplings FF-Series for Multiplate

	Body Size	Connection A	Hex mm	L mm	D mm	D1 mm	Working Press. connect. in bar	Version	Seal	Part Number
 <p>Female Thread</p>	1/2"	G 1/2	40	82	52	47	400	for Multiplate	NBR/PUR	FF5010 CE
	1/2"	G 1/2	40	82	52	47	400	for Multiplate	FKM	FF5010 CEV
	3/4"	G 3/4	50	98	66	60	400	for Multiplate	NBR/PUR	FF7510 CE
	3/4"	G 3/4	50	98	66	60	400	for Multiplate	FKM	FF7510 CEV

Plugs FF-Series Pressure Eliminator for Multiplate

	Body Size	Connection A	Hex mm	L mm	D mm	D1 mm	Working Press. connect. in bar	Version	Seal	Part Number
 <p>Female Thread</p>	1/2"	G 1/2	36	120	52	47	400	Press. El. f. Multiplate	NBR/PUR	FF5021 CE
	3/4"	G 3/4	50	146	66	60	400	Press. El. f. Multiplate	NBR/PUR	FF7521 CE

Lubrication Nipples FF-Series

	Body Size	Version	L mm	D mm	Part Number
	1/2"	for coupling	48	29	GRF5
	3/4"	for coupling	52	38	GRF7
	1"	for coupling	52	50	GRF10

Seal-Kit

FF-Series

Body Size	Version	Material	Part Number
1/4"	for plugs	NBR	FF2500-PSNPU
3/8"	for plugs	NBR	FF3800-PSNPU
1/2"	for plugs	NBR	FF5000-PSNPU
1/2"	for plugs	FKM	FF5000-PSV
3/4"	for plugs	NBR	FF7500-PSNPU
3/4"	for plugs	FKM	FF7500-PSV
1"	for plugs	NBR	FF10000-PSNPU
1"	for plugs	FKM	FF10000-PSV

Dust Protection

FF-Series

Body Size	Version	L mm	D mm	Material	Color	Part Number
1/4"	for coupling	190	24	PVC	Blue	FF2516
1/4"	for plug	190	24	PVC	Blue	FF2526
3/8"	for coupling	190	28	PVC	Blue	FF3816
3/8"	for plug	190	28	PVC	Blue	FF3826
1/2"	for coupling	220	28	PVC	Blue	FF5016
1/2"	for plug	220	28	PVC	Blue	FF5026
3/4"	for coupling	250	42	PVC	Blue	FF7516
3/4"	for plug	250	42	PVC	Blue	FF7526
1"	for coupling	290	51	PVC	Blue	FF10016
1"	for plug	290	51	PVC	Blue	FF10026



Further colors on request.



Parker快速接头授权分销商联系方式：

信德迈科技(北京)有限公司 CNMEC Technology Company

地址：北京市朝阳区望京街10号望京SOHO-T1-C座2115室

邮编：100102

电话：010-8428 2935,8428 3983

手机：139 1096 2635

Http：//www.cnmec.biz

E-mail：sales@cnmec.biz

传真：010-8428 8762