

# MPI Tube Fittings

Medium Pressure (15K) Tube Connections for the Process and Offshore Industries



Does your current system call out 15,000 PSI rating?

Our MPI-Medium Pressure Inverted Fittings offer the installer secure, leak free connections in systems that require operating pressures in the range of 6,000 to 15,000 psi. MPI Fittings are designed to handle liquids, gases, or chemicals and can be used on a wide variety of tubing materials



## Contact Information:

Parker Hannifin Corporation  
**Instrumentation Products Division**  
1005 A Cleaner Way  
Huntsville, AL 35805

phone 256.881.2040  
fax 256.881.5730  
ipdsales@parker.com

[www.parker.com/ipdus](http://www.parker.com/ipdus)



## Product Features:

- Supercase Technology
- Double Ferrule
- Longer Thread engagement
- Molybdenum Disulfide coated nut
- Inverted body design

## Product Benefits:

- Corrosion Resistant Ferrule for a strong, mechanical hold on the tubing
- Proven design. Non-Interchangeable with standard tube fittings
- Improved resistance to pressure and load on the ferrules
- Excellent, low torque performance. Prevent galling, easier assembly, and multiple remakes
- Stronger body for higher pressure ratings

ENGINEERING YOUR SUCCESS.