

Nominal Diameter

5,5 = 25 mm²

Rectus Tema Series

1400energy
saver**Other designs in series 1400**

The following other designs can be found from page:

- Safety Self-Venting P. 224

Interchangeability (KA only)

- Rectus 24
- Industr. Interchange 1/4"
- US-MIL-SPEC-C-4109
- ISO 6150 B
- Cejn 310
- Hansen 3000
- Faster
- Gromelle 600
- JWL 521 + JWL 531

RectusTema premium industrial coupling 1/4" according to ISO 6150 B. Suitable for compressed air applications with greater than average air consumption. Coupling system with single-hand operation. Ultra High Flow valve for optimum flow and low pressure drop.

Series 1400 with additional end connections available on request.

Dust Protections (P. 250)
for Coupling Part.-No. SK23S

Working Temperature*

-20°C up to +100°C (NBR)
depending on the medium.

* For temperatures below -20°C and over +100°C and depending on the medium, other seal variants (FKM, EPDM, FFKM) are available.

**Working Pressure****

35 bar

** maximum static working pressure with design factor 4 to 1.

Material

Coupling: Brass nickel plated,
Steel QPQ treated

Plug: Steel nickel plated or Brass

Seals: NBR

Technical Description

Connecting Force 0 bar: 35 N


Connecting Force 6 bar: 75 N

Vacuum Coupling: 96%

Vacuum connected: 96%

Flow diagrams




Air





Couplings – with valve




Series 1400KA

	Connection A	HEX mm	L mm	L1 mm	D mm	Version	Part Number
 <p>Male Thread</p>	R 1/4	19	65	12	23		1400KAAK13SPN
	R 3/8	19	65	12	23		1400KAAK17SPN
	R 1/2	22	59,5	17	23		1400KAAK21SPN
 <p>Female Thread</p>	G 1/4	19	59	9	23		1400KAIW13SPN
	G 3/8	19	59	9	23		1400KAIW17SPN
	G 1/2	24	62	12	23		1400KAIW21SPN
 <p>Hose Barb</p>	6 mm	19	80	25	23		1400KATF06SPN
	8 mm	19	80	25	23		1400KATF08SPN
	10 mm	19	80	25	23		1400KATF10SPN
	13 mm	19	80	25	23		1400KATF13SPN



Plugs – without valve

Series 23SF

	Connection A	HEX mm	L mm	L1 mm	D mm	Version	Part Number
 <p>Male Thread</p>	R 1/8	13	39	9		Steel	23SFAK10SXN
	R 1/4	14	42	12		Steel	23SFAK13SXN
	G 1/4	14	42	12		Brass	23SFAW13MXX
	R 3/8	17	42	12		Steel	23SFAK17SXN
	G 3/8	17	42	12		Brass	23SFAW17MXX
 <p>Female Thread</p>	R 1/2	22	48	17		Steel	23SFAK21SXN
	G 1/8	14	36	9		Steel	23SFIW10SXN
	G 1/4	17	36	9		Steel	23SFIW13SXN
	G 3/8	19	36	9		Steel	23SFIW17SXN
 <p>Hose Barb</p>	G 1/2	24	39	12		Steel	23SFIW21SXN
	6 mm		51	25	14	Steel	23SFTF06SXN
	6 mm		51	25	14	Brass	23SFTF06MXX
	8 mm		51	25	14	Steel	23SFTF08SXN
	9 mm		51	25	14	Steel	23SFTF09SXN
	9 mm		51	25	14	Brass	23SFTF09MXX
	10 mm		51	25	14	Steel	23SFTF10SXN
	13 mm		51	25	14	Steel	23SFTF13SXN