

Quik Draw™



*Polyester
Single Jacket
Forestry Hose*



Small Diameter, Lightweight Polyurethane Lined

Quik Draw™ is a small diameter, lightweight, compact single jacket fire hose using standard $\frac{3}{4}$ " brass Garden Hose Thread (GHT) fittings having a working pressure of 150 psi (1035 kPa). This high tenacity filament polyester, polyurethane lined hose can be ordered with or without Dura-Cote treatment that minimizes abrasion and pinholing. With 50' of Quik-Draw weighing only 1.25 lbs. and a coil diameter of around 9", this hose can be taken almost anywhere.

LIGHTWEIGHT POLYESTER SINGLE JACKET



SIZE	MAX. OPERATING PRESSURE	BURST	WEIGHT (50' Coupled)
IN	PSI (kPa)	PSI (kPa)	LBS (KG)
5/8"	150 (1035)	600 (4140)	1.25 (0.6)

How to Order

TYPE	HOSE I.D. x HOSE LENGTH	COLOR	COUPLING SIZE	THREAD TYPE	COUPLING MATERIAL
2F	06 = 5/8" 50 = 50'	W = White (Uncoated)	07 = 3/4"	GH = Garden Hose	B = Brass

Part No. Example: 2F06X50W07GHB =

2F Quik Draw Hose, 5/8" ID by 50' Length, White, 3/4" Brass Garden Hose Threaded Coupling

Construction

Polyester Single Jacket
Polyurethane Lined Liner

Coating:

Optional Dura-Cote (with color)

Temperature Range

-40° to 150°F (-40° to 65°C)

Couplings

Brass Garden Hose

Colors

UNCOATED

